

MODEL	GSN 1580	GIN 1580	GIN 1380	GIN 1220
DISHWASHER				
COLOR OPTIONS				
Stainless steel-X	•	•	•	•
Stainless steel with black inlay-XB	•	•	•	-
Aluminium-L	•	-	-	-
White-Alu-A	•	-	-	•
TYPE OF APPLIANCE				
Semi-integrated/fully integrated/free standing	-/•	•/-	•/-	•/-
Energy efficiency class	A	A	A	A
Energy consumption (kW)	1.05	1.05	1.05	1.05
Cleaning performance	A	A	A	A
Drying performance	A	A	A	A
Standard capacity-settings	12	12	12	12
Water consumption (lt)	9	9	13	15
Duration minimum (min.)	30	30	30	30
Duration ref. prog. (min.)	163	163	170	150
Estimated consumption per year (220 standard programs)				
Energy consumption (kW)	231	231	231	231
Water consumption (lt)	1980	1980	2860	3300
Noise level (in under-counter position) dB (re1 pW)	46	47	48	50
FEATURES				
Container inox/plastic	•/-	•/-	•/-	•/-
Inner door inox/plastic	•/-	•/-	•/-	•/-
Cabinet coated	•	•	•	•
Cleaning programs	9	9	8	5
Program temperatures (°C)	70/65/55/50/40/35	70/65/55/50/40/35	70/65/55/50/40/35	70/55/50/35
Water softener fitted	•	•	•	•
Salt indicator	Electronic	Electronic	Electronic	Electronic
Rinse aid indicator	Electronic	Electronic	Electronic	Electronic
Water safety system	AquasafePlus	AquasafePlus	AquasafePlus	AquasafePlus
Protection against water back flow	•	•	•	•
ENERGY CONNECTION				
Voltage/frequency (V/Hz)	230/50	230/50	230/50	230/50
Connected value (kW)	2	2	2,2	2,2
Max. current intensity (A)	10	10	10	10
WATER CONNECTION				
Water supply connection G3/4	•	•	•	•
Warm water connection (°C)	60	60	60	60
WATER DRAIN				
Maximum possible height from floor to water connection (cm)				
Maximum possible hose length (cm)	110	110	110	110
	400	400	400	400
DIMENSIONS				
Niche dimensions (HxWxD) mm		820-920x600x570	820-920x600x570	820-920x600x570
Height (cm)	85	82	82	82
Width (cm)	59,8	59,8	59,8	59,8
Depth including wall distance (cm)	57	55	55	55
Depth with opened door (cm)	115	115	115	115
Height adjustable (cm)	+1,5	82-92	82-92	82-92
Weight (packed/unpacked) kg	53/56	42/45	42/45	42/45

MODEL	GVN 1380	GIS 1380	GIS 1220
DISHWASHER			
COLOR OPTIONS			
Stainless steel-X	-	•	•
Stainless steel with black inlay-XB	-	-	-
Aluminium-L	-	-	-
White-Alu-A	-	white	white
TYPE OF APPLIANCE			
Semi-integrated/fully integrated/free standing	-/•	•/-	•/-
Energy efficiency class	A	A	A
Energy consumption (kW)	1.05	1.01	1.01
Cleaning performance	A	A	A
Drying performance	A	A	A
Standard capacity-settings	12	10	10
Water consumption (lt)	13	12	12
Duration minimum (min.)	30	30	30
Duration ref. prog. (min.)	170	170	170
Estimated consumption per year (220 standard programs)			
Energy consumption (kW)	231	222	222
Water consumption (lt)	2860	2640	2640
Noise level (in under-counter position) dB (re1 pW)	48	48	50
FEATURES			
Container inox/plastic	•/-	•/-	•/-
Inner door inox/plastic	•/-	•/-	•/-
Cabinet coated	•	•	•
Cleaning programs	8	8	5
Program temperatures (°C)	70/65/55/50/40/35	70/65/55/50/40/35	70/55/50/35
Water softener fitted	•	•	•
Salt indicator	Electronic	Electronic	Electronic
Rinse aid indicator	Electronic	Electronic	Electronic
Water safety system	AquasafePlus	AquasafePlus	AquasafePlus
Protection against water back flow	•	•	•
ENERGY CONNECTION			
Voltage/frequency (V/Hz)	230/50	230/50	230/50
Connected value (kW)	2,2	2,2	2,2
Max. current intensity (A)	10	10	10
WATER CONNECTION			
Water supply connection G3/4	•	•	•
Warm water connection (°C)	60	60	60
WATER DRAIN			
Maximum possible height from floor to water connection (cm)			
Maximum possible hose length (cm)	110	110	110
	400	400	400
DIMENSIONS			
Niche dimensions (HxWxD) mm	820-920x600x570	820-920x450x570	820-920x450x570
Height (cm)	82	82	82
Width (cm)	59,8	44,8	44,8
Depth including wall distance (cm)	55	55	55
Depth with opened door (cm)	115	115	115
Height adjustable (cm)	82-92	82-92	82-92
Weight (packed/unpacked) kg	42/45	38/40	38/40